

Company _____

Address _____

Name / Customer No. _____

 RAMPF Formen GmbH
 Altheimer Straße 1
 89604 Allmendingen
 Germany

P +49 7391 505-0
F +49 7391 505-142
 @ info@rampf.de

www.rampf.com

| Pos. | Description / VPE | Technical data | Use | Item |
|------|--|---------------------------|---|------|
| 1 | Angle grinder MSf (a) 680 d | 2300W / 220V | Welding over of welding seams, surface grinding | |
| 2 | Long-necked grinder MSf v 649 | 750W / 220V | Grinding areas which are difficult to access | |
| 3 | Cylindrical grinder MSh 648 | 650W / 220V | Polishing, slurring | |
| 4 | Air-operated power wrench ATLAS LT V 38 | max. M12 | Tamper shoe assembly | |
| 5 | Extension 2 x 150 mm | Air-operated power wrench | Tamper shoe assembly | |
| 6 | Impact wrench CP-9540-RSR | | e.g. tamper part installation | |
| 7 | Face wheel grain 40 / 20 items | Ø 110 mm | Surface grinding | |
| 8 | Face wheel grain 80 / 10 items | Ø 80 mm | Surface grinding | |
| 9 | Rough wheel / 10 items | Ø 178 x 6 mm | Rough grinding | |
| 10 | | Ø 150 x 6 mm | Rough grinding | |
| 11 | Cutting-off wheel / 25 items | Ø 178 x 2.5 mm | Abrasive cutting | |
| 12 | | Ø 150 x 2.5 mm | Abrasive cutting | |
| 13 | End mill cutter | Form ZYA 1020 | Are required for cylindrical grinder | |
| 14 | | Form WRC 1020 | Use depends on the processed contours | |
| 15 | | Form K(SPG)1020 | | |
| 16 | Abrasive pencil / 10 items | Ø 16 x 45 | Polishing, grinding with cylindrical grinder | |
| 17 | | Ø 25 x 45 | Polishing, grinding with cylindrical grinder | |
| 18 | Electrodes | UTP 630 Ø 2.5 mm | Root welding | |
| 19 | | UTP 630 Ø 2.5 mm | Root welding | |
| 20 | | UTP 65 D Ø 2.5 mm | Root welding, e.g. frame parts | |
| 21 | | UTP 65 D Ø 3.25 mm | Root welding, e.g. frame parts | |
| 22 | | UTP 673 Ø 2.5 mm | Hard-facing | |
| 23 | | UTP 673 Ø 3.25 mm | Hard-facing | |
| 24 | Heavy wire electrodes for the inert gas shielded arc welding; 15 kg per roll | S G 3, 1.2 mm 15 kg | Welding of, e.g. frame parts | |
| 25 | | 1.4370; 1.2 mm 15 kg | Root welding | |
| 26 | | 1.4718; 1.2 mm 15 kg | Hard-facing | |
| 27 | Extensions for Impact wrench | 1/2" x 7" | Tamper shoe assembly | |
| 28 | Socket | 19 mm 1/2" | Tamper shoe assembly | |
| 29 | | 24 mm 1/2" | e.g. tamper part installation | |
| 30 | Open-end wrench | 19 mm /24 mm | e.g. Tamper shoe assembly | |
| 31 | Ring wrench | 19 mm /24 mm | e.g. Tamper shoe assembly | |
| 32 | Feeler band / 5m rolls | 0.4 mm | Checking the tamper shoe tolerance | |
| 33 | | 0.8 mm | Checking the tamper shoe tolerance | |
| 34 | Hand magnet 400A | 200 x 50 mm | Insert tamper shoes | |
| 35 | Hand magnet 600A | 200 x 70 mm | Insert tamper shoes | |
| 36 | Thermo-wax crayon | Up to 152°C | Checking the parts temperature | |
| 37 | Low angle | 200 mm | Evenness, control angularity | |